

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Belco Petr. Corp.</u>		Lease <u>Autry</u>		Well # <u>1</u>	
Location of Well	Unit <u>E</u> <u>2310N</u> <u>990W</u>	Section <u>20</u>	Township <u>22</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	Type of Equipment <u>Rotary</u>				

APPROVED CASING PROGRAM 6-13-78

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>11"</u>	<u>8 5/8"</u>	<u>24</u>		<u>400</u>	<u>200 Sacks</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.5</u>		<u>3400</u>	<u>700</u>

Casing Data:

Surface 9 joints of 8 5/8 inch 24 # Grade K-55
(Approved) (Rejected)

Inspected by M.S. date 9/18/78

Cementing Program

Size of hole 11" Size of Casing 8 5/8 Sacks cement required 250

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 400' Set 400' Feet of 8 5/8 Inch 24 # Grade K-55

New-used csg. @ 400' with 250x200 sacks neat cement around shoe

+ sac additives

Plug down @ 1:00 (AM) (PM) Date 9/19/78

Cement circulated yes No. of Sacks 30

Cemented by Dowell Witnessed by Mike Stubbfield

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 3 control logs @ 380'-360'-320'

Last log break @ 210'