

DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

Superseded by
C-102 and C-101
Effective 1-1-65

JAN 15 1979

50. Indicate Type of Lease
State ☐ Fee ☒

51. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON OIL & GAS OPERATIONS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPER OR REPAIR OR TO ABANDON OR TO PLUG A WELL OR TO OPERATE A WELL IN A RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Belco Petroleum Corporation

3. Address of Operator
10,000 Old Katy Rd. Suite 100, Houston, Texas 77055

4. Location of Well
UNIT LETTER B 2310 FEET FROM THE East LINE AND -330 FEET FROM THE North LINE, SECTION 29 TOWNSHIP 22-S RANGE 27-E NE 1/4.

15. Elevation (Show whether DF, RT, GR, etc.)
3140.7 GR

7. Unit Agreement Name

8. Form or Lease Name
Walker-Coleman

9. Well No.
1

10. Field and Pool, or Wildcat
Undesignated S. Carlsbad
Cherry Canyon

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugging Procedure:

1. Set cement retainer @ + 3200'. Squeeze perforations w/100 sx cmt.
2. Cut casing at freepoint, & spot a 100 sx. cmt. plug.
3. Pull casing to 500' & spot a 100 sx. cmt. plug from 300' to 500'.
4. Pull & LD casing
5. Spot a 10 sx. cmt. plug @ the surface.
6. Erect monument & clean up location.

Well Facts:

1. TD 3400'
2. Perforations - 3284' - 94'.
3. 8-5/8" Surface casing set @ 401' w/250 sx cmt. Cement circulated
4. 5 1/2" production casing set at 3400' w/475 sacks cement. TOC 1500
5. Anticipated plugging date - March 1, 1979.

* 5 1/2" casing stub plug & 8 3/8" shoe plug must be pumped thru 2" tubing & tagged.

* Intervals between plugs filled w/ mud.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J.C. Ball TITLE Production Engineer DATE 1/11/79

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JAN 15 1979

CONDITIONS OF APPROVAL, IF ANY:
* 2" tubing shoe.

NEWBY NMACO...
I hereby...