

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

DEC 18 1978

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Gomez
9. Well No. 1
10. Field and Pool, or Wildcat Und. Herradura Bend-Delaware
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- ☐

2. Name of Operator
Amoco Production Company ✓

3. Address of Operator
P.O. Drawer "A", Levelland, Texas 79336

4. Location of Well
UNIT LETTER K 1650 FEET FROM THE West LINE AND 2310 FEET FROM
THE South LINE, SECTION 5 TOWNSHIP 23-S RANGE 28-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3014.1 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Evaluated well and determined well was not commercially productive. Propose to P X A well using the following procedure: Spot 25 sx (200') Class H cement plug 2600'-2400'; ~~spot 15 sx (100') Class H cement plug 700'-600'~~; Spot 10 sx (80') Class H cement plug at surface. Erect P X A marker and clean and level location. * spot 25 SX 325-500

Csg. in hole 8 7/8" - 390 - Circ.
5 1/2" 3500 circ.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Hennis Evans TITLE Assit. Admin. Analyst DATE December 14, 1978

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE DEC 19 1978

CONDITIONS OF APPROVAL, IF ANY:
O & 4 NMOCC-A 1-Susp 1-Houston 1-DE * as noted above