

DEPARTMENT OF THE INTERIOR (Reverse Side)
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

LEASE DESIGNATION

NM-26684

6. IF INDIAN, ALLOTTED OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gourley-Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Herradura Bend (Delaware)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T-22S, R-28E

12. COUNTY OR PARISH 13. STATE

Eddy Co.

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

RECEIVED

2. NAME OF OPERATOR

Orla Petco, Inc.

SEP - 8 1978

3. ADDRESS OF OPERATOR

P.O. Box 1383, Midland, Texas 79702

D. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

990' FNL & 330' FEL of Sec. 31, T-22S, R-28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

3065' G.L. 3066' D.F.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANN

(Other) Setting and cementing casing X

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well on August 11, 1978 at noon.

9/1/78

Ran Peabody-Vann Gamma-Ray Log. Log TD-2507'. Bailed 90' of oil and 10 gals. of water. Ran 4 1/2" 9.5# J-55 casing to a total depth of 2494', cemented with 500 sx of Class "C" 2% CaCl cement. Plug down at 2:20 p.m. WOC 22 hrs.

9/2/78

Start drilling out plug at noon today. T/Delaware - 2378'
T/Delaware Sand- 2478'
T/Ramsey Sand- 2500'
Base of Salt- 2110'

18. I hereby certify that the foregoing is true and correct

SIGNED

James C. Ketchum Jr.

TITLE

Field Manager

DATE

Sept. 2, 1978

(This space for Federal or State office use)

APPROVED BY

Joe J. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

SEP 7 - 1978

CONDITIONS OF APPROVAL, IF ANY: