

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

NOV 13 1978

O.C.C.

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Amoco Production Company ✓	5. State Oil & Gas Lease No.
3. Address of Operator P.O. Drawer "A", Levelland, Texas 79336	7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>K</u> <u>1880</u> FEET FROM THE <u>South</u> LINE AND <u>2080</u> FEET FROM THE <u>West</u> LINE, SECTION <u>22</u> TOWNSHIP <u>23-S</u> RANGE <u>28-E</u> N.M.P.M.	8. Farm or Lease Name Brantley Gas Com
	9. Well No. 1
	10. Field and Pool, or Wildcat Und. Morrow
11. Elevation (Show whether DF, RT, GR, etc.) 3032.5 RDB	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to TD 11,332' and on 10-26-78 set 7 5/8 39# S-95 LT & C (5846') 33.7# S-95 LT&C (5846') casing at 11,332'. Cemented with 2000 sx Trinity Lite with 3/4 of 1% CFR-2 and 1/4# Flocele and 350 sx Class H with 3/4 of 1% CFR-2. Found top of cement at 3780' by temperature survey. PD 3:00 p.m. 10-26-78. WOC 3 days. Tested casing 1500# for 30 minutes. Test O.K.. Reduced hole to 6 1/2" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dennis Evans TITLE Assist. Admin. Analyst DATE 11-9-78

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE NOV 14 1978

CONDITIONS OF APPROVAL, IF ANY:

O+4-NMOCC-A 1-Susp 1-Div 1-DE 1-Roy G. Barton, Jr.  
Box 978 Hobbs New Mexico 88240