- which make a real control of the c	レ
NY, OF COPH'S RECEIVED	Form C-103
DISTRIBUTION	Supersedes Old C+102 and C+103
NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	
LAND OFFICE	5a, Indicate Type of Lease
LAND OFFICE	State Fee X
OPERATOR //	5. State Cil & Gas Lease No.
DEC - 7 1978	- Committee Comm
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DIREL OR TO CELEBR OR PLUG BACK TO A DIFFERENT RESERVOIR.  (LE MAPELICATION FOR PERMIT IN TERM CHOIL FOR SUCH PROPOSALS)	
	7. Unit Agreement Name
OIL CAS X OTHER. ARTESIA, OFFICE	
. ) dime of Cymrator	8, Form or Lease Name
Amoco Production Company	Brantley Gas Com
Address of Control	9. Well No.
P.O. Drawer "A", Levelland, Texas 79336	1
Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER K 1880 FEET FROM THE SOUTH LINE AND 2080 FEET FROM	Und. Morrow
THE West LINE, SECTION 22 TOWNSHIP 23-S RANGE 28-E NMPM	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3032.5 RDB	Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Ot	her Data
	T REPORT OF:
PERFORM PEMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OFNS.	PLUG AND ABANDONMENT
FULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER	
OTHER	
OTHER	estimated date of starting any transport
	estimated date of starting any proposed
OTHER	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe: roposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
OTHER	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
OTHER	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
7. Describe increased or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.  Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m Released rig 11:50 p.m. 11-26-78.	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
OTHER	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.
Drilled to TD 13,126' and on 11 -24-78 ran 5" 17.93# N-80 liner set the liner set at 11,008'. Cemented with 350 sx Class H cement plus 3/6 of 1% CFR-2 and 5# KCL/sx. Circulated cement. PD 3:15 p.m. 11-Drilled out 758' cement 10,230'-10,988'. Tested with 1500# for 30 m Released rig 11:50 p.m. 11-26-78.	at 13,126'. Top of 3/10 of 1% Halid 22A, 24-78. WOC 18 hours.

O&4 NMOCD-A 1-Susp 1-Houston 1-DE