

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 26 days after the completion of any newly-drilled or deepened well. It must be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including full test reports. All formations shall be full name and be listed in the order of lithologically drilled wells; true vertical depth shall also be reported. If no lithologic completion, Items 22 through 24 shall be reported for each zone. The form is to be filed in quadruple except on state land, where six copies are required. See Rule 11.5.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Bell Canyon	2978'	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Cherry Canyon	3968'	T. Strawn	11,504'	T. Rutland-Frontland		T. Penn. "C"	
B. Brushy Canyon	5004'	T. Atoka	11,705'	T. Pictured Cliffs		T. Penn. "D"	
T. Bone Springs	6656'	T. Miss		T. Cliff House		T. Leadville	
T. 3rd Bone Springs	9562'	T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres		T. Simpson		T. Gallup		T. Ignacio Quartz	
T. Glerieta		T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota			
T. Blinberry		T. Gr. Wash		T. Morrison			
T. Tubb		T. Granite		T. Todilto			
T. Drinkard		T. Delaware Sand		T. Entrada			
T. Abo		T. Bone Springs		T. Wingate			
T. Wolfcamp	10,717'	T. Morrow Line	12,385'	T. Chino			
T. Penn.	11,372'	T. Morrow Clastics	12,608'	T. Permian			
T. Cisco (Bough C)				T. Penn. "A"			

OIL OR GAS SANDS OR ZONES

No. 1, from	None	to		No. 4, from		to	
No. 2, from		to		No. 5, from		to	
No. 3, from		to		No. 6, from		to	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	None	to		feet.	
No. 2, from		to		feet.	
No. 3, from		to		feet.	
No. 4, from		to		feet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	452	452	Red Bed				
452	1495	1043	Salt				
1495	2159	664	Anhydrite				
2159	2950	791	Anhydrite + Salt				
2950	4228	1278	Anhydrite + Sand				
4228	5612	1384	Lime + Sand				
5612	6093	481	Lime				
6093	7830	1737	Lime + Sand				
7830	9834	2004	Lime + Sand + Shale				
9834	11202	2368	Lime + Shale				
11202	11563	361	Shale				
11563	13399	1836	Shale + Lime				