

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.T.O.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		RECEIVED	7. Unit Agreement Name
2. Name of Operator Amoco Production Company ✓		JUL 17 1980	8. Farm or Lease Name Teledyne 20 Gas Com.
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		O. C. D.	9. Well No. 1
4. Location of Well UNIT LETTER C, 660 FEET FROM THE North LINE AND 2080 FEET FROM THE West LINE, SECTION 20 TOWNSHIP 23 RANGE 29 NMPM.		ARTESIA, OFFICE	10. Field and Pool, or Wildcat Und. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 2963.3. GL		12. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 7-5-80, Kenai Big West Drilling Co. (Rig #23) spudded a 20" hole at 3:00 p.m. Drilled to a TD of 402' and ran 65# H40 16" casing set at 399'. Cemented with 500 SX Class C 2% CACL. Circulated 60 SX. Plugged down at 2:30 a.m. 7-6-80. WOC 20 hr. Tested casing to 600#. Test OK. Reduced hole to 14-3/4" and resumed drilling.

0+5-NMOCD, A 1-Hou 1-Susp 1-LBG 1-Getty

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 7-16-80

APPROVED BY Trish Williams TITLE JUL 17 1980 DATE OIL AND GAS INSPECTOR

CONDITIONS OF APPROVAL, IF ANY: