

CONTRIBUTOR	
TYPE	
DATE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

MAY 11 1979

3a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No. LG-3006

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

1. Well Name W. O. B. 1000, Midland, Texas 79702	7. Unit Agreement Name
2. Other: ☐ Dry Hole	8. Farm or Lease Name South Horseshoe Bend 10 Com.
3. Location of Well 1980 FEET FROM THE West LINE AND 957 FEET FROM	9. Well No. 1
4. Line, Section 10 TOWNSHIP 24S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Wildcat (Morrow)
11. Elevation (Show whether DF, RT, GR, etc.) 4039' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF: 4-10-79

REPAIR REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
WELL OF ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

13. Describe and Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.)

ID 11990

- 4-21-79 - Spotted all perfs from 7988' - 8050' w/50 sx Cl H cmt. w/1/2# Celloflake per sx mixed at 15.5 gal; displ. w/37 bbls 9.6# gelled brine.
- 5-1-79 - Tagged top via tbq to 3000 psi. Held ok. Circ. hole w/10#/gal. gel brine. Pulled tubing and packer. Ran temp survey from 7100' - 7818'.
- 5-3-79 - Cut P casing at 5560'.
- 5-4-79 - Finished pulling 7-inch casing. Put in well: 9767' Left in well: 4207'.
- 5-5-79 - Spotted all Cl H neat at 5600' - Tagged top plug at 5500'. Spot 60 sx Cl C neat cmt. at 3310'. Spot 60 sx Cl C neat cmt. at 2950'.
- 5-7-79 - Spotted all Cl C neat at 2980'.
- 5-8-79 - Tagged top of plug at 2780'. Ran tubing to 475' circ. hole w/mud laden fluid. Spot 60 sx Cl C cmt. plug 475'-375'. (OVER)

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: Betty A. Gildon TITLE: Regulatory Clerk DATE: May 10, 1979

APPROVED BY: _____ TITLE: _____ DATE: _____

15. COMMENTS, IF ANY:

5-8-79 continued.
 Removed top, wellhead and spool; spot 35 sx plug at surface, topped out w/ 100 lb. plug.
 Welded plug over casing and installed dry-hole marker.
 Well was shut in 5-8-79.

Steel casing	Put in Well	Left in Well
13-3/4"	425'	425'
9-5/8"	2900'	2900'
7"	9767'	4207'
4-1/2" Liner	2415'	2415'
Top of liner at 9575' - Bottom of liner at 11,990'		