N 3, OF COPIES RECEIVED DISTRIBUTION SANTA FE	3		NEW MEXICO O	R 05 N	REATION COMMISSION		Form C -103 Supersedes Old C-102 and C-103 Effective 1-1-65	
FILE	11					r		
U.S.G.S.	İ			MAR	1 1070		5a. Indicate Type of	
LAND OFFICE	1			MAK	1 1979		State	Fee X
OPERATOR	1/						5. State Oil & Gas L	ease No.
					C. C.			
(DO NOT USE THIS FO	SU SU	NDRY	NOTICES AND REPOR	RTS ON	WELLS Ach to a Different Reservoir.			
· · · · · · · · · · · · · · · · · · ·	. [X		OTHER-				7, Unit Agreement No	ame
Name of Crierator							8. Farm or Lease Na	me
Delta Dr	·i11	ing (Company				Carrasco (Comm
Address of Operator				······			9. Well No.	<u></u>
	x 3	467.	Midland, Texas	9702			1	
Location of Well					· · · · · · · · · · · · · · · · · · ·		10. Field and Pool,	or Wildcat
F		19	180	lorth	LINE AND 1980	TET FROM	Wildcat-Mc	orrow
UNIT LETTER	(FLET FROM THE	· · · · · · · · ·		LET PROM		
THE West	LINE,	SECTION	14TOWNSHIP_	235	RANGE 28E	NMPM.		
mmmmm	\overline{m}	$\overline{\Pi}$	15. Elevation (Show	v whether	DF, RT, GR, etc.)		12. County	
	111,	////	300)1 GR			Eddy	
-10.	Ch				ature of Notice, Report	t of Oth	er Data	
NOT			ENTION TO:	icate it	-		REPORT OF:	
NOTI			ENTION TO:		56555			
PERFORM REMEDIAL WORK			PLUG AND ARA	•DON	REMEDIAL WORK		ALTERING	
TEMPORARILY ABANDON	4				COMMENCE DRILLING OPHS.	H	PLUG AND	ABANDONMENT
PULL OR ALTER CASING			CHANGE PLANS		CASING TEST AND CEMENT JOB	LÄI		~
OTHER		<u>-</u>			OTHER	. <u> </u>		L_J

17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled $6\frac{1}{2}$ " hole to 13100'. After logging, ran 69 jts $4\frac{1}{2}$ " P-110 Hydril liner as follows:

	Length	Depth
Liner Hanger	28.41	10075.15
68 jts 4½" P-110 Liner	2949.30	13052.86
Catcher Collar	1.32	13054.18
1 jt 4½" P-110 Liner	43.97	13098.15
Guide Shoe (Baker)	1.85	13100.00

Cemented with 500 sacks Class H with 3/10 of 1% CFR-2, 6/10 of 1% Halad 22A, and 5# KCL per sack. Ran 30 sacks of TLW with 3/4 of 1% CFR-2 for scavenger slurry ahead of cement. Had good circulation during cementing. H cement mixed at 15.8# per gallon. Bumped plug with 3000 psi at 4:45 PM on 2/26/79. Closed by-pass, and set packoff on liner hanger with 50,000#. Pulled out of liner 30 stands and started laying down drill pipe. Did not attempt to reverse out cement. Set on wellhead and released rig at 6:00 AM 2/28/79.

is. Thereby certify that the information above is true and comple Λ	te to the t	est of my knowledge and belief.		
IGNED Mon Juck Ron Lechwar	TITLE	Project Manager	DATE	2/28/79
APPROVED AV W, a, Gresset	TITLE_	SUPERVISOR. DISTRICT II	DATE	MAR 2 1979
CONDITIONS OF APPROVAL, IF ANYI				