

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Dry Hole  
2. NAME OF OPERATOR  
Coquina Oil Corporation  
3. ADDRESS OF OPERATOR  
P. O. Drawer 2960, Midland, TX. 79702  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FEL & 1980' FSL  
AT TOP PROD. INTERVAL: --  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE

NM 28632

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Patterson Federal

9. WELL NO.

1

ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20-23S-23E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4247' GL 4262' KB

RECEIVED

FEB 1 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

(NOTE: Report of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Cement plugs were set on January 16, 1979. Total depth 10,170'.

Set 60 sx. cement plug 9570-9420'; 65 sx. cement plug 8180-7980'; 55 sx. cement plug 7125-7075'; 50 sx. cement plug 5400-5250'; 35 sx. cement plug 3900-3800'; 40 sx. cement plug 2455-2355'; and 10 sx. cement plug at surface. Drlg. mud between cement plugs in hole is 9.5#/gal., 40 sec. Vis. with 6.5 cc water loss.

Rig released and P&A complete at 6:00 P.M., January 16, 1979. Dry hole marker installed. Pits are fenced until dry enough to close and restore.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Leland H. Stall*

TITLE

Drlg. Manager

DATE

1-31-79

(This space for Federal or State office use)

APPROVED BY

L. H. STALL

TITLE

DATE

JAN 29 1980

CONDITIONS OF APPROVAL, IF ANY: