C -4.

DEPARTMENT OF THE INTERIOR  DITATION COMMENTS  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	Form Approved. Budget Bureau No. 42-R1424  5. LEASE LC-069142-A  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drillor to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)  1. oil gas well other  2. NAME OF OPERATOR Perry R. Bass 3. ADDRESS OF OPERATOR P.O. Box 2760, Midland, TX 79702  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FSL & 1780' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	7. UNIT AGREEMENT NAME Big Eddy Unit 8 FARM OR LEASE NAME Big Eddy Unit 9 WELL NO. 68 10. FIELD OR WILDCAT NAME Undesignated (Delaware) 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 10, T22S, R28E 12. COUNTY OR PARISH Eddy New Mexico 14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3114' GL 3130' KB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.) Springs

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Work began 11/21/83 Spot 20 sx Class "H" neat cmt from 10710-10530' (mix 15.6 ppg & 1.18 ft $^3$ /sk). PU & spot 20 sx Class "H" neat cmt from 9590-9410' (same mix). PU & spot 20 sx Class "H" near cmt from 6440-6260' (same mix). PU to 6260' & circulate hole clean. PU to 6163' & spot 100 gals 15% HCl acid. Perforate Bone Springs 6101, 6105, 6109, 6114, 6120, 6123, 6127, 6130, 6134, 6138, 6142, & 6146' using 4" casing gun (12 holes). RIH with packer & 2-3/8" N-80 tbg to 6020'. Landed and set pkr @ 6020' with SN @ 6016'. Acidize perfs 6101-6146' w/5000 gals 15% HCl acid and additives. Swab interval. Rec 3 BW w/only trace of condensate. Last swab runs were dry. Shut in well. Prep to recomplete to Delaware.

Subsurface Safety Valve: Manu. and Type	Set @	, Ft.
18. Thereby certify that the foregoing is true and correct  SIGNED John D. Redgers, TITLE Sr. Production Engage	3/29/84	
/ ACCEPTED FOR RECLAMINE page for Federal or State office use)		
APPROVED BY FINANT 7 1984	DATE	