PLUG AND ABANDON THE TOTAL WORK	
SUNDRY NOTICES AND REPORTS ON WELLS Amoco Production Company Amoco Production Company P. O. Box 68, Hobbs, NM 88240 1, Figuration (Show whether DF, RT, GR, etc.) 2967.8 GR Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: **CHARGE PLANS** CHARGE PLANS** **CHARGE	t
SUNDRY NOTICES AND REPORTS ON WELLS Amoco Production Company Amoco Production Company Amoco Production Company Amoco Production Company And Brantley B Substitute Substitute And Brantley B S	
SUNDRY NOTICES AND REPORTS ON WELLS ON OF DETAILS AND REPORT OF SUBSEQUENT RE	I Louso
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS Amoco Production Company State of the production of the p	Foe X
SUNDRY HOTICES AND REPORTS ON WELLS Amoco Production Company Allocation classifications of the second sec	Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS Comparison of the Company	
Amoco Production Company Amoco Production Company Amoco Production Company Brantley B J. Well 150. 1 10. Field and Fool Unit Little J. 1980 FEET FROM THE SOuth LINE AND 1980 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 23-S RANGE 28-E MARK. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JOB. MILLING OPPS. CASING TEST AND CEMENT JOB. MILLING OPPS.	
Amoco Production Company Amoco Production Company Annoco Production Company Description of Company 10. Field and Fool 11. Location of Action of Action of Action of Company The East 124 13. Field and Fool 14. Field and Fool 15. Field and Fool 16. Field and Fool 17. Field and Fool 18. Field and Fool 19. F	
Amoco Production Company Amoco Production Company P. O. Box 68, Hobbs, NM 88240 Libertine of Lyell ONLY LETTER J. 1980 FEET FROM THE SOuth LINE AND 1980 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 23-S RANGE 28-E NOTICE OF INTENTION TO: PLUC AND ABANDON FEET FROM THE SUBSEQUENT REPORT OF: PLUC AND ABANDON FEET FROM THE SUBSEQUENT REPORT OF: OTHER COMMENCE DRILLING OPPS. CHANGE PLANS COMMENCE DRILLING OPPS. COMENCE DRILLING OPPS. COMMENCE DRILL	.cin.e
Anoco Production Company P. O. Box 68, Hobbs, NM 88240 1. Location of the Mark 1980 The East 1980 Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu approx. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test 0K. Reduced.	lame
P. O. Box 68, Hobbs, NM 88240 P. O. Box 68, Hobbs, NM 88240 Interpolation of Acid The East Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: Subsequent Report of Subs	Gas Com.
P. O. Box 68, Hobbs, NM 88240 LLOCATION CETTER J 1980 FEET FROM THE SOuth LINE AND 1980 FEET FROM Und. Morro THE East LINE, SECTION 24 TOWNSHIP 23-S RANGE 28-E MARKE. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SERFORM REMODIAL WORK SUBSEQUENT REPORT OF: CHANGE PLANS CHANGE PLANS COMMERCE DRILLING OPHS. CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add Casing foot OTHER TO of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu approx. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the result of the casing with 2000# for 30 min. Test OK. Reduced the casing with 2000# for 30 min. Test OK. Reduced the casing with 2000# for 30 min.	005 00111
THE EAST LINE, SECTION 24 TOWNSHIP 23-S RANGE 28-E NUMBER. 15. Flevation (Show whether DF, RT, GR, etc.) 2967.8 GR Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: CHANGE PLANS CHA	
THE East LINE, SECTION 24 TOWNSHIP 23-S RANGE 28-E NAME. 15. Flevation (Show whether DF, RT, GR, etc.) 2967.8 GR Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: PLUG AND ABANDON SUBSEQUENT REPORT OF: CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add Casing foot OTHER TO add Casing foot OTHER TO add Casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plug approx. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Reduced to the contract of the contr	, or Wildcat
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CHANGE	N
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CASING TEST AND CEMENT JOB X CHANGE PLANS CASING TEST AND CEMENT JOB X CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JOB X CASING TE	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON CHANGE PLANS CHA	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: PENFORM REMEDIAL WORK CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add casing foot of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/8 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Surv approx. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	44444
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add casing foot NOTICE OF INTENTION TO: CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add casing foot NOTICE OF INTENTION TO: CHANGE PLANS OTHER TO add casing estimated date of significant plans of the pertinent details, and give pertinent dates, including estimated date of significant plans of the pertinent dates. Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/8 S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	(7777)
PLUG AND ABANDON REMEDIAL WORK COMMENCE ORILLING OPNS. CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add casing foot work) SEE HOLE 1103. Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test 0K. Redu	
TEMPORABLEY ABANDON CHANGE PLANS CHANGE PLANS COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB X OTHER TO add casing foot OTHER TO add casing foot OTHER Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/8 S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Surv approx. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	
Commence of Illing Opns. CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER TO add casing foot OTHER TO add casing foot OTHER OTHER OTHER OTHER TO add casing foot OTHER OTHER TO add casing foot OTHER OTHER OTHER OTHER OTHER TO add casing foot OTHER OTHER OTHER OTHER OTHER TO add casing other of structure is commented and other	G CASING
CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JOB X TO add casing foot other To add casing foot To add casing foot To add casing foot other To add casing foo	O ABANDONMENT
Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	
Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/8 S-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	age X
Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/8-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	
Drilled to a TD of 10070' and ran 5975' of 7-5/8" 39# S-95 LT&C and 4090' of 7-5/8-95 LT&C casing set at 10065'. Cemented with 1700 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	arting any proposed
S-95 LT&C casing set at 10065'. Cemented with 1/00 sx Trinity Lite cement with 3 and 1/4# Flocele/sx and 300 sx Class H cement with 3/4% CFR-2 and 5# KCL/sx. Plu 10:15 P.M. 12-24-79. Cement did not circulate. Found top of cement by Temp Survapprox. 3350'. WOC 48 hrs. Tested casing with 2000# for 30 min. Test OK. Redu	
	gged down ey at
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Localus Inc. Assistant Admin. Analyst one 1-8-	30
	ii 1 0 1980

0+4 NMOCD-A. 1-Hou. 1-Susp. 1-BD