

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUL 15 1980

O. C. D.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (C-101) FOR SUCH PROPOSALS.

Oil Well ☐ Gas Well ☐ OTHER: Dry

Name of Operator: The Eastland Oil Company

Address of Operator: P.O. Drawer 3488, Midland, Texas 79702

Location of Well:

UNIT LETTER N 330 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 29 TOWNSHIP 22S RANGE 28E N.M.P.M.

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

6. Form of Lease Name
C. R. Lopez "D"

9. Well No.
1

10. Field Name or Name of Well
Herradura Bend
Cherry Canyon

12. County
Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3019' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPS. ☐ PLUG AND ABANDONMENT ☒

ULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOB ☐

OTHER ☐

SUBSEQUENT REPORT OF:

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On May 13, 1980, ran 2 1/2" tubing open ended to 3296' and loaded hole with 10 ppg mud.
Set cement plugs as follows:

3296' to 3196' with 35 sx class C cement
2506' to 2406' with 35 sx class C cement
2190' to 2090' with 35 sx class C cement
425' to 325' with 50 sx class C cement

Tagged plug @ 389' after 4 hours. Recemented 389' to 300' with 60 sx class C cement. Tagged plug at 300' May 14, 1980. Set plug from 40' to surface with 15 sacks. Plugging complete at 10:30 a.m. 5-14-80. Left 376' 8 5/8", 24# casing in well set @ 376' and cement circulated w/250 sx.

Location has been cleared and leveled, anchors removed, and dry-hole marker installed.
It is ready for inspection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: [Signature] TITLE: Superintendent DATE: July 11, 1980

APPROVED BY: _____ TITLE: _____ DATE: _____

CONDITIONS OF APPROVAL, IF ANY: