

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUL 15 1980

O. C. D.

ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR OPERATIONS TO DRILL OR TO REOPEN OR WELD BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT TO DRILL OR TO REOPEN OR WELD BACK TO A DIFFERENT RESERVOIR.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Dry	50. Indicate Type of Lease State ☐ Fee ☒
2. Name of Operator The Eastland Oil Company	51. State Oil & Gas Lease No.
3. Address of Operator P.O. Drawer 3488, Midland, Texas 79702	7. Unit Agreement Name
4. Location of Well UNIT LEASE N 330 FEET FROM LINE South LINE AND 1980 FEET FROM THE West END, SECTION 29 TOWNSHIP 22S RANGE 28E N.M.P.M.	8. Name of Lease Holder C. R. Lopez "D"
10. Elevation (Show whether DF, RT, GR, etc.) 3019' GR	9. Well No. 1
12. County Eddy	10. Field Name Herradura Bend Cherry Canyon

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On May 13, 1980, ran 2 1/2" tubing open ended to 3296' and loaded hole with 10 ppg mud.
Set cement plugs as follows:

3296' to 3196' with 35 sx class C cement
2506' to 2406' with 35 sx class C cement
2190' to 2090' with 35 sx class C cement
425' to 325' with 50 sx class C cement

Tagged plug @ 389' after 4 hours. Recemented 389' to 300' with 60 sx class C cement. Tagged plug at 300' May 14, 1980. Set plug from 40' to surface with 15 sacks. Plugging complete at 10:30 a.m. 5-14-80. Left 376' 8 5/8", 24# casing in well set @ 376' and cement circulated w/250 sx.

Location has been cleared and leveled, anchors removed, and dry-hole marker installed.
It is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Henry L. Neal* TITLE Superintendent DATE July 11, 1980

APPROVED BY *Mike Stappfeld* TITLE OIL AND GAS INSPECTOR DATE AUG 28 1980

CONDITIONS OF APPROVAL, IF ANY: