

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert Depth	R E C T A N G U L A R C O O R D I N A T E S	Dogleg Deg/100ft	Vert Sect
9849.00	20.40	81.78	9643.13	59.25 S 988.31 E	1.84	988.31
9945.00	20.39	81.97	9733.11	54.52 S 1021.43 E	0.07	1021.43
10041.00	16.80	85.23	9824.09	51.03 S 1051.83 E	3.89	1051.83
10137.00	13.60	87.31	9916.72	49.35 S 1076.94 E	3.38	1076.94
10233.00	10.20	92.95	10010.65	49.26 S 1096.71 E	3.74	1096.71
10329.00	6.60	93.48	10105.60	50.03 S 1110.71 E	3.75	1110.71
10425.00	4.40	104.54	10201.15	51.29 S 1119.78 E	2.53	1119.78
10521.00	3.10	111.31	10296.95	53.16 S 1125.76 E	1.43	1125.76
10617.00	3.10	113.48	10392.81	55.13 S 1130.56 E	0.12	1130.56
10713.00	3.30	112.96	10488.66	57.25 S 1135.49 E	0.21	1135.49
10906.00	4.60	107.73	10681.20	61.77 S 1147.98 E	0.70	1147.98
11002.00	4.20	93.08	10776.92	63.13 S 1155.15 E	1.24	1155.15
11098.00	2.70	106.58	10872.74	63.97 S 1160.83 E	1.77	1160.83
11194.00	2.10	122.56	10968.66	65.56 S 1164.48 E	0.93	1164.48
11290.00	1.90	133.20	11064.60	67.59 S 1167.12 E	0.44	1167.12
11386.00	1.50	137.98	11160.56	69.62 S 1169.12 E	0.44	1169.12
11482.00	1.10	152.44	11256.53	71.37 S 1170.39 E	0.54	1170.39
11578.00	1.20	201.22	11352.51	73.12 S 1170.45 E	0.99	1170.45
11674.00	1.40	194.84	11448.49	75.19 S 1169.79 E	0.26	1169.79
11770.00	1.40	203.16	11544.46	77.40 S 1169.03 E	0.21	1169.03
11866.00	1.60	240.51	11640.43	79.14 S 1167.40 E	1.02	1167.40
11962.00	1.80	241.32	11736.39	80.52 S 1164.91 E	0.21	1164.91
12059.00	1.90	239.06	11833.34	82.08 S 1162.20 E	0.13	1162.20
12154.00	1.60	239.35	11928.29	83.57 S 1159.70 E	0.32	1159.70
12251.00	1.60	274.00	12025.26	84.16 S 1157.19 E	0.98	1157.19

All data is in feet unless otherwise stated.
 Coordinates from slot #1 and TVD from rotary table.
 Bottom hole distance is 1150.22 on azimuth 94.24 degrees from wellhead.
 Vertical section is from N 0.00 E 0.00 on azimuth 90.00 degrees.
 Calculation uses the minimum curvature method.
 Presented by Baker Hughes INTEQ