

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-015-22902

5. Indicate Type of Lease

STATE ☐ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

PARDUE "34"

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

BK EXPLORATION CORPORATION OGRID 002433

3. Address of Operator

810 S CINCINNATI STE 20B TULSA OK 74119-1612

4. Well Location

Unit Letter H : 2310 feet from the NORTH line and 660 feet from the EAST line

Section 34

Township 23-S Range 28-E NMPM EDDY County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3035' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

8-1-2000 Rigged up Patterson #141. Commenced drilling with 8.5" bit. NUBOP.

8-3-2000 Drilled out cement abandonment plugs to 4735'. By Halliburton, spotted cement plug (130 sxs. "C") @ 4457-4727'. Wait on cement.

8-4-2000 Drilled cement plug with 8.5" bit to 4498'.

8-5-2000 With 7.875" bit, drilled deviated section at 4498' to 4580'. Continued drilling new hole to new total depth 6350'. Ran deviation surveys in new hole.

8-10-2000 Set used 5.5", 15.5# - 17# casing @ 0-6348'. By BJ Services, cemented with 250 sxs. lite "C" cement, followed by 150 sxs. "C" cement. Plug down, floats held. NDBOP, NUWH. RD. Waiting on pulling unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Brad D Burks TITLE PRESIDENT DATE 8-18-2000

Type or print name BRAD D. BURKS

918.582.3855

Telephone No.

(This space for State use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

AUG 31 2000