

2/5F


UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ P&A  
2. NAME OF OPERATOR  
Yates Petroleum Corporation  
3. ADDRESS OF OPERATOR  
207 So. 4th St., Artesia, NM 88210  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1650 FSL & 2310 FEL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☒  
(other) ☐ ☐



5. LEASE  
NM 24152  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
North Crooked Creek KG Federal Com  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Wildcat Morrow  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit J, Sec. 27-T23E-R24E  
12. COUNTY OR PARISH 13. STATE  
Eddy NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3873' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged well as follows:

- Plug #1: 9830-9500' w/25 sx Class "H" cement  
Plug #2: 8330-8000' w/25 sx Class "H" cement  
Plug #3: 7000-6900' w/35 sx Class "C" (across 4-1/2" stub)  
Plug #4: 4100-4000' w/35 sx Class "C" cement  
Plug #5: 2550-2450' w/35 sx Class "C" (across 8-5/8" stub)  
Plug #6: 50' - Surface w/15 sx Class "C" cement

Cut and pulled 6950' of 4-1/2" casing. Heavy mud placed between plugs.

Verbal approval for plugging given by Mr. Peter Chester, MNS, Roswell to Mr.

Eddie Mahfood, Yates Petroleum Corporation. Regulation abandonment marker will

be installed and surface restoration will be in accordance with MMS-BLM requirements.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineering Secty DATE 7-8-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 7-13-82  
CONDITIONS OF APPROVAL, IF ANY:

