

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-711	

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

JUL 19 1979

Name of Operator
Harvey E. Yates Company ✓
Address of Operator
P. O. Box 1933, Roswell, N. M. 88201
Location of Well

O. C. C.
ARTESIA, OFFICE

7. Unit Agreement Name
8. Farm or Lease Name
Amoco 22 State
9. Well No.
2
10. Field and Pool or Wildcat
Und. S. Carlsbad Mor.

UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 22 TOWNSHIP 23S RANGE 27E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3147.8' GL

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Run production casing, etc. ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-3-79 Ran 140 joints (5609') 8 5/8"OD 32#, 28#, and 24#**, 8-R,
ST&C new R-3 casing set at 5609' KB and cemented in 2 stages:
1st stage:

780 Sx Halliburton Lite w/8# salt and 1/4# Flocele/Sx and
200 Sx Cl H Neat. PD at 10:00 pm 7-3-79. Dropped opening bomb
and opened LV tool at 1973' KB.

2nd stage:

1000 Sx Halliburton Lite w/8# salt, 1/4# Flocele and 3#
Gilsonite/Sx and 100 Sx Cl H Neat. PD at 3:35 am 7-4-79.
Closed tool, bumped plug w/1500 psi. Released pressure. Held
OK. Cement did not circulate. Ran temperature survey. TOC
at 105'.

7-4-79 WOC 24 hours. Pressured up on casing to 1800 psi. Held OK.

**56 jts (2818.98') 32#, 24 jts (1019.69') 28#, 60 jts (1770.33') 24#

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ENGINEER Paul J. Lardice TITLE Engineer

DATE July 18, 1979

PROVED BY W. A. Grasset

TITLE SUPERVISOR, DISTRICT II

DATE JUL 20 1979