

DELTA RIG 3 INVENTORY

DRAWORKS

- Emsco C-1 type III
- Grooved for 1-3/8" drill line
- Parmac Model 481 Hydromatic Brake

DERRICK

- Lee C. Moore
- 142 ft. high
- 780,000 lb. static hook load

SUBSTRUCTURE

- Lee C. Moore
- 22 ft. high
- 850,000 lb. casing capacity
- simultaneous with 350,000 lb.
- setback capacity

POWER SOURCE

- 3 - Caterpillar D-398 TA (diesel)
- Horsepower - 2331

PUMPS

- 1300 HP triplex
- Gardner-Denver PZ-9 1000 HP
- High volume - low pressure mud mixing system

DRILL STRING

- 12,000' - 4-1/2" O.D., 16.6#/ft., Gr.E, 4-1/2"XH
- by 6" O.D. tool joints
- Other grades of pipe available
- Standard size collars available through 8"

PREVENTERS

- 2 - Cameron, model QRC, 10", 5000 psi
- 1 - Hydril, model GK, 10", 5000 psi
- 1 - Payne Accumulator, 80 gallons capacity with 5 stations

OTHER EQUIPMENT

- Crown block-Lee C. Moore 7-42" sheaves
- Traveling block-Emsco, model NB42
- Hook-Byron Jackson, model 4300
- Light plants-two, Caterpillar, 90 KW., 110/220 volts A.C.
- Swivel-National, model R-3
- Mud tanks-two, 7'X6'X48'
- Lights-Snelson, vapor proof
- Rotary table-National, 20-1/2"
- Bunk house-12'X44', wheeled
- Shale shaker-Link Belt, model NRM 145,S-66
- Radio-Motorola, 100 watt
- Crown-O-Matic