STATE OF NEW MEXICO	
ENERGY AND MINERALS DEPARTMENT	
	Form C-103
SANTA FE, NEW MEXICO 8750ED	Revised 10-1-78
	5a. Indicate Type of Lease
	State X Fee
SaN 0 1980	5. State Oil & Gas Lease No.
	L-4764
SUNDRY NOTICES AND REPORTS ON WELLS OF C. D.	Million Manna Million
SUNDRY NOTICES AND REPORTS ON WELLS C. D. 100 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO GEEFLE OR PLUG BACK TO APTERMENDERTEVOIR.	
1	7. Unit Agreement Name
OIL GAS X OTHER-	· •
2. Name of Operator	B. Farm or Lease Name
The Superior Oil Company	Oscar State
3. Address of Operator	9. Well No.
P. O. Box 71, Conroe, Texas 77301	1
4. Location of Weil	10. Field and Pool, or Wildcat
UNIT LETTER <u>G 1980</u> FEET FROM THE N LINE AND <u>1980</u> FEET FROM	Wildcat (Morrow)
THEE LINE, SECTION 36 TOWNSHIP 245 RANGE 29E NMPM.	
11. Elevation (Show whether DF, RT, GR, etc.)	12. County
16. З102 GR 3123 КВ	Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:
PERPORM REMEDIAL WORK	
	ALTERING CASING
COMMENCE DRILLING OFNS.	PLUG AND ABANDONMENT
CASING TEST AND CEMENT JOB [X]	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including e work) SEE RULE 1103.	stimated date of starting any proposed
Spud date: 10-19-79 Resource Drig Co. Din #4	•
Spud date: 10-19-79, Resource Drlg. Co. Rig #4. Ran 13-3/8" Csg. (4 KB, and cemented w/530 sys class "C" accord W/20 0 class "	48#, H-40, ST&C) to 518'
KB, and cemented w/530 sxs class "C" cement W/2% CaCl, & 5# Coalite. & circulated cement to surface WOC 45 brs. No pt and state	Had full returns
& circulated cement to surface. WOC 45 hrs. No pt-csg set just above lost circ. zone.	
Lost mud returns at 623' and Oct. 22 & mixed 3 lost circulations pills - dry drilling to	
a beach pipe out. 23. Tur 1041. KB ('outd not reserve d'it i state a -	
0.000 $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$ $0.000$	
The off off and the second and of the second	junk from hole
at 2227' KB.	Jam From hore
Drilled to 3300' W/12-1/4" bit on Nov. 13 & ran 10-3/4" Csg. to 3292	KB. Cemented with 700
and doy do posmin torrowed w/200 SXS Class "("" No returne during and	
pressure 2200#. Second stage of 200 sax (308 CF) thru DV tool at 554	' with no returns.
Third stage of 50 sax thru 1" pipe at 84' in annulus with no returns. 85 sax (113 CF) thru 1"pipe at 84 in annulus with no returns.	Fourth stage of
85 sax (113 CF) thru l"pipe at 84 in annulus with good cement returns WOC 27-1/4 Hrs. Drilled out cement & shoe & pt at 3300' TD w/1500#-C	& hole stayed full.
	ок.
3. I hereby certify that the information above is true and complete to the beat of my knowledge and belief.	
Kally	
F. H. Speers Regulatory Eng. Specialist	1 0 00
Title accounter specialist	DATE 1-8-80
I wale -	
PROVED BY U. G. Gressett HILE SUPERVISOR, DISTRICT I	DATE JAN 1 1 1980
INDITIONS OF APPROVAL, IF ANY	DATE VMIN 100

NMOCC (3), GET, CHQ, RG, CF, AGP, GAB