

N. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
APR 2 1980
O. C. D.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name South Culebra Bluff
8. Farm or Lease Name South Culebra Bluff Unit
9. Well No. 4
10. Field and Pool, or Wildcat South Culebra Bluff Bone Springs
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Delta Drilling Company ✓
3. Address of Operator P.O. Box 3467, Midland, Texas 79702
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>560</u> FEET FROM THE <u>East</u> LINE. SECTION <u>23</u> TOWNSHIP <u>23S</u> RANGE <u>28E</u> N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 2987.1

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/26/80

Killed well with 500 BBls. of 4% KCL fresh water. Pulled wellhead and installed BOPs. Pulled 2-3/8" tubing. Ran 97 JTS of 4-1/2" 10.5# K-55 ST&C liner as follows:

	Length	Depth
TIW Liner Hanger	8.95	5795.22
96 JTS. 4-1/2" 10.5# K-55	3965.85	9761.07
Float collar & plug catcher	2.43	9763.50
Shoe joint	35.02	9798.52
Guide shoe	1.48	9800.00

Cemented with 475 SX HLC with 3# KCL and 3/10 of 1% Halad 22-A, mixed at 12.7#/gal. Displaced with fresh water. Plug down at 3 p.m. 3/28/80. Had good circulation throughout job. Circulated 150' cement above liner top. Ran wireline bailer on 4/5/80 and tagged cement at 4762'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ron Lechwar TITLE Project Manager DATE 3/31/80
APPROVED BY W. A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE APR 9 1980
CONDITIONS OF APPROVAL, IF ANY: