

C/SF

UNITED STATES N.M.O.C.D. COPY

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different
Artesia, New Mexico Form 9-831-C for such proposals.1. oil well ☐ gas well ☐ other ☒ Dry Hole

2. NAME OF OPERATOR

The Superior Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 71, Conroe, Texas 77301

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2030' FNL & 1980' FWL Sec.25

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Vertical

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐OTHER ☐

RECEIVED

FEB 25 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-831-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugging Procedure

1. Perfs 11450-11499 squeezed w/20 sxs cement.
 2. Perfs 9305-9342 O/A squeezed with 50 sxs class H cement.
 3. Plugs as follows: (4852' of 7-5/8" csg recovered.)
 - 9000'-8840' (30 sacks class "H")
 - 4870'-4710' (60 sacks class "H")
 - 3550'-1720' (60 sacks class "H")
 - 50'-10' (20 sacks class "H")
- Csg cut 4' below GL & 1/4" steel plate welded on stub.
Installed marker.

Surface Safety Valve Model and Type

Serial

Fl.

18. I hereby certify that the foregoing is true and correct

SIGNED

G. Bannantine

TITLE

Reg. Group Mgr

DATE

2-20-80

APPROVED BY

Dan Wood

TITLE

ARTESIA, NEW MEXICO AREA

DATE

10-22-85

CONDITIONS OF APPROVAL IF ANY