

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION	TRUE VERTICAL DEPTH FEET	VERTICAL SECTION FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOG LEG SEVERITY DEG/100FT
5900.	0 30	S 1 W	5899.57	-46.17	46.26 S	0.3
6000.	0 30	S 11 W	5999.56	-47.04	47.13 S	0.1
6100.	0 30	S 10 W	6099.56	-47.90	47.98 S	0.0
6200.	0 15	S 35 W	6199.56	-48.50	48.58 S	0.3
6300.	0 30	S 3 W	6299.55	-49.12	49.20 S	0.3
6400.	0 45	S 26 W	6399.55	-50.17	50.25 S	0.3
6500.	0 30	S 11 W	6499.54	-51.20	51.28 S	0.3
6600.	0 30	S 19 W	6599.54	-52.05	52.12 S	0.1
6700.	0 45	S 9 W	6699.53	-53.11	53.18 S	0.3
6800.	0 30	S 15 W	6799.52	-54.18	54.24 S	0.3
6900.	0 15	S 20 W	6899.52	-54.80	54.87 S	0.3
6950.	0 30	S 3 W	6949.52	-55.13	55.19 S	0.5
6974.	2 15	N 15 E	6973.51	-55.18	55.25 S	11.4
7067.	3 45	N 9 E	7066.38	-50.41	50.49 S	1.6
7160.	4 45	N 1 E	7159.12	-43.54	43.63 S	1.2
7253.	7 15	N 1 W	7251.60	-33.82	33.91 S	2.7
7346.	8 45	N 5 W	7343.70	-20.91	20.99 S	1.7
7439.	9 0	N 11 W	7435.58	-6.73	6.78 S	1.0
7532.	10 0	N 13 W	7527.30	8.24	8.23 N	1.1
7625.	11 15	N 9 W	7618.71	25.02	25.06 N	1.6
7718.	11 45	N 12 W	7709.84	43.21	43.29 N	0.8
7811.	12 30	N 14 W	7800.76	62.18	62.32 N	0.9
7904.	12 45	N 6 W	7891.52	82.14	82.32 N	1.9
7997.	14 0	N 11 W	7981.99	103.37	103.59 N	1.8
8090.	14 30	N 10 W	8072.13	125.83	126.10 N	0.6
8183.	15 45	N 11 W	8161.91	149.63	149.96 N	1.4
8276.	17 0	N 11 W	8251.13	175.30	175.70 N	1.3
8369.	19 0	N 15 W	8339.57	203.21	203.69 N	2.5
8462.	20 30	N 17 W	8427.10	233.31	233.90 N	1.8
8555.	20 0	N 18 W	8514.35	263.88	264.60 N	0.7