

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	VERTICAL SECTION FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOG LEG SEVERITY DEG/100FT
3000.	1 30	S 49 E	2999.77	-24.14	24.14 S 0.69 W	0.4
3100.	1 30	S 40 E	3099.74	-25.99	26.00 S 1.15 E	0.2
3175.	1 45	S 45 E	3174.71	-27.54	27.57 S 2.58 E	0.4
3250.	1 15	S 60 W	3249.68	-29.22	29.26 S 2.36 E	3.2
3300.	0 45	S 39 E	3299.67	-29.98	30.01 S 2.22 E	3.1
3400.	1 0	S 30 E	3399.66	-31.23	31.27 S 3.09 E	0.3
3500.	0 45	S 51 E	3499.65	-32.37	32.42 S 4.07 E	0.4
3600.	0 45	S 40 E	3599.64	-33.27	33.34 S 5.00 E	0.1
3700.	0 45	S 30 E	3699.63	-34.33	34.41 S 5.75 E	0.1
3800.	0 30	S 31 E	3799.62	-35.27	35.35 S 6.31 E	0.3
3900.	0 15	S 20 E	3899.62	-35.85	35.94 S 6.59 E	0.3
4000.	0 15	S 45 E	3999.62	-36.21	36.30 S 6.82 E	0.1
4100.	0 30	S 20 E	4099.62	-36.76	36.85 S 7.17 E	0.3
4200.	0 0	0	4199.62	-37.16	37.26 S 7.32 E	0.5
4300.	0 0	0	4299.61	-37.16	37.26 S 7.32 E	0.0
4400.	0 0	0	4399.61	-37.16	37.26 S 7.32 E	0.0
4500.	0 45	S 10 E	4499.61	-37.81	37.90 S 7.43 E	0.7
4600.	0 15	S 5 E	4599.61	-38.67	38.77 S 7.55 E	0.5
4700.	0 30	S 0 E	4699.60	-39.33	39.42 S 7.57 E	0.3
4800.	0 30	S 3 W	4799.60	-40.20	40.30 S 7.55 E	0.0
4900.	0 0	0	4899.60	-40.63	40.73 S 7.53 E	0.5
5000.	0 30	S 1 W	4999.59	-41.07	41.17 S 7.52 E	0.5
5100.	0 30	S 19 W	5099.59	-41.93	42.02 S 7.37 E	0.2
5200.	0 15	S 16 W	5199.59	-42.55	42.65 S 7.17 E	0.3
5300.	0 15	S 9 W	5299.59	-42.98	43.07 S 7.08 E	0.0
5400.	0 0	0	5399.59	-43.19	43.28 S 7.05 E	0.2
5500.	0 15	S 32 W	5499.58	-43.38	43.47 S 6.93 E	0.2
5600.	0 0	0	5599.58	-43.56	43.65 S 6.82 E	0.2
5700.	0 30	S 9 W	5699.58	-44.00	44.08 S 6.75 E	0.5
5800.	0 45	S 5 E	5799.58	-45.08	45.17 S 6.71 E	0.3