

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	VERTICAL SECTION FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOG LEG SEVERITY DEG/100FT
0.	0 0	0	0.00	0.00	0.00	0.0
100.	0 0	0	100.00	0.00	0.00	0.0
200.	0 15	N 85 E	200.00	0.02	0.22 N	0.2
300.	0 15	N 37 W	300.00	0.35	0.35 N	0.4
400.	0 15	N 11 W	400.00	0.74	0.74 N	0.1
500.	0 30	N 87 E	500.00	1.20	1.20 N	0.6
600.	0 0	0	599.99	1.23	1.22 N	0.5
700.	0 0	0	699.99	1.23	1.22 N	0.0
800.	0 15	N 79 E	799.99	1.28	1.26 N	0.2
900.	0 15	N 83 E	899.99	1.35	1.33 N	0.0
1000.	0 30	S 52 E	999.99	1.19	1.16 N	0.4
1100.	0 30	S 3 W	1099.99	0.43	0.40 N	0.5
1200.	0 15	S 25 W	1199.98	-0.20	0.23 S	0.3
1300.	0 45	S 1 E	1299.98	-1.05	1.08 S	0.5
1400.	0 45	S 23 W	1399.97	-2.33	2.36 S	0.3
1500.	0 30	S 11 W	1499.96	-3.38	3.40 S	0.3
1600.	1 0	S 5 E	1599.96	-4.68	4.70 S	0.5
1700.	0 45	S 13 W	1699.94	-6.20	6.22 S	0.4
1800.	0 45	S 23 W	1799.93	-7.45	7.46 S	0.1
1900.	0 30	S 3 E	1899.93	-8.51	8.52 S	0.4
2000.	0 15	S 11 W	1999.93	-9.16	9.17 S	0.3
2100.	1 0	S 25 W	2099.92	-10.20	10.21 S	0.8
2200.	1 0	S 23 W	2199.90	-11.80	11.80 S	0.0
2300.	1 0	S 25 W	2299.89	-13.41	13.40 S	0.0
2400.	1 0	S 17 W	2399.87	-15.04	15.03 S	0.1
2500.	0 45	S 33 W	2499.86	-16.43	16.40 S	0.3
2600.	0 45	S 15 W	2599.85	-17.63	17.59 S	0.2
2700.	0 45	S 33 W	2699.84	-18.82	18.79 S	0.2
2800.	1 0	S 18 E	2799.83	-20.29	20.25 S	0.8
2900.	1 30	S 35 E	2899.81	-22.23	22.20 S	0.6