

10. Blowout Preventer Program is attached.
11. Type and characteristics of the proposed circulating medium or mediums to be employed for rotary drilling, and the quantities and types of mud and weighting material to be maintained.
- 0-400' Native mud and fresh water.
 - 400'-2700' Commercial mud and brine water.
 - 2700'-10900' Commercial mud and brine with fresh water make up to maintain safe hole conditions.
 - 10900'-TD Commercial mud and cut brine w/KCL for 3% system.
12. Testing, logging and coring programs to be followed with provisions made for required flexibility.
- | | |
|-------------------------------------|------------|
| Comp Neutrom Form Density w/Caliper | Surf to TD |
| Dual Laterolog Micro SFL | Surf to TD |
13. Any anticipated abnormal pressure or temperatures expected to be encountered or potential hazards, such as hydrogen sulfide gas, along with plans for mitigating such hazards.

None anticipated

14. Anticipated starting date and duration of operation.

9-15-79	11-15-79
---------	----------

15. Other facets of the proposed operation operator wishes to point out for the Geological Survey's consideration of the application.

Request exemptions from the painting stipulations of Sec. 102 (a) (8) of the "Federal Land Policy and Management Act of 1976" to paint any tanks, separators, and treaters required for the production of this well, Amoco's standard gray color. If a pumping unit is required for the continued production of this well, it will be painted black with orange safety color coding which conforms with your current painting guidelines.