

U.C.C.D. COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Amoco Production Company
3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1650' FSL x 1980' FEL, Sec. 20  
AT SURFACE: (Unit J, NW/4 SW/4)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to a TD of 2705' and ran 10-3/4" casing set at 2705'. Cemented with 2245 s Howco Lite cement with additives and 200 sx Class C cement with 2% CACL. Plug down 6:30 P.M. 11-2-79. Circulated 200 sx. WOC 18 hrs. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 9-1/2" and resumed drilling.

RECEIVED

NOV 16 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bob Davis TITLE Assist. Admin. Ana DATE 11-12-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACTING DISTRICT ENGINEER

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

0+4 USGS-A, 1-Hou, 1-Susp, 1-BD, 1-Marathon, 1-Bass