

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well <input type="checkbox"/>	gas well <input checked="" type="checkbox"/>	other <input type="checkbox"/>
2. NAME OF OPERATOR Amoco Production Company		
3. ADDRESS OF OPERATOR P. O. Box 68 Hobbs, NM 88240		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1650' FSL & 1980 FEL. Sec. 20 AT TOP PROD. INTERVAL: (Unit J, NW/4, SW/4) AT TOTAL DEPTH:		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

## SUBSEQUENT REPORT OF:

<input type="checkbox"/>	RECEIVED
<input checked="" type="checkbox"/>	AUG 1 1980
<input type="checkbox"/>	U.S. GEOLOGICAL SURVEY
<input type="checkbox"/>	ARTESIA, NEW MEXICO

5. LEASE NM-0415239-6	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Federal AE	
9. WELL NO. 1	
10. FIELD OR WILDCAT NAME Und. Morrow	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 20-22-28	
12. COUNTY OR PARISH Eddy	13. STATE NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3077 GR	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pulled tubing and packer and set a cast iron bridge plug at 11600' and capped with 35' of cement. Perforated 11116'-11122' with 4 JSPF. Ran tubing, packer and tailpipe. Packer set at 10198'. Acidized with 2000 gal. 15% HCL acid. Currently swab testing.

0+5-USGS, A      1-Hou      1-Susp      1-LBG

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bob Davis TITLE Admin. Analyst DATE 7-30-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

