

NMCC. COPY

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FSL X 1980' FEL, Sec. 20
AT TOP PROD. INTERVAL: (Unit J, NW/4, SW/4)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Recompletion

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
MAY 8 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM-04151239-B
6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
7. UNIT AGREEMENT NAME
MAY 13 1981
8. FARM OR LEASE NAME
Federal AE G. C. D.
9. WELL NO.
1 ARIZONA OFFICE
10. FIELD OR WILDCAT NAME
Und. Delaware
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
20-22-28
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3077' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 4-2-81. Pulled tubing, packer, and tailpipe. Set a cast iron bridge plug at 5950' and capped with 35' cement. Perforated 3324'-3340' with 2 JSPF. Run tubing, packer, and packer. Packer set at 3167'. Tailpipe set at 3266'. Run cement retainer and set at 3227'. Pressure casing to 500# X squeeze 700 sacks Class 'C' cement. Cement circ. out surface casing. Drilled out to 3410'. Run tubing and packer and set packer at 3170'. Acidize with 2500 gal. 7-1/2% HCL with additives. Currently swab testing.

0+4-USGS, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-GPM

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Greg Mitchell TITLE Admin. Analyst DATE 5-5-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE MAY 8 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO