

P.O. BOX 98 LOCO HILLS, NEW MEXICO 88255 LOCO HILLS (505) 677-2111 1 (800) 748-1972 LOVINGTON (505) 396-3331 1 (800) 748-2084

NMOCD-EPA 2040 S. Pacheco Santa Fe, New Mexico 87505 January 06, 2000

Attn. Roger Anderson

This is a proposal only. The monitor wells for the Eugenie #2 will not be drilled until the NMOCD approves this plan or gives I & W, Inc. a plan of their own specifications of their approval.

The monitor wells will be drilled with air. Diameter of hole will be 4 7/8". Casing will be 2" flush joint monitor casing with 10° of slotted monitor with a plug on bottom. Installed on top will be water tight locking caps with bolt down manhole. The well will also be gravel packed with bentonite grout on top. Cement curbing will be placed around each manhole.



These three wells are to be drilled to  $65^{\circ}$ . We will install monitor casing which is EPA specification. The cellar, once all operations have been completed to plug well bore, will be filled with cement. A dry hole marker will be installed on the Eugenie #2.

Your comments on this proposal would be appreciated. If you have any questions or comments please contact me at (505) 885-6663.

Sincerely.

George E. Parchman Manager



GP/lr

ARTESIA (505) 746-4214 1 (800) 748-1972

CARLSBAD (505) 885-6663 1 (800) 658-2739



P.O. BOX 98 LOCO HILLS, NEW MEXICO 88255 LOCO HILLS (505) 677-2111 1 (800) 748-1972

January 06, 2000

LOVINGTON (505) 396-3331 1 (800) 748-2084

NMOCD-EPA 2040 S. Pacheco Santa Fe, New Mexico 87505

CARLSBAD

(505) 885-6663

1 (800) 658-2739

ARTESIA

(505) 746-4214

1 (800) 748-1972

Attn. Roger Anderson

This is a proposal only. The monitor wells for the Eugenie #2 will not be drilled until the NMOCD approves this plan or gives I & W, Inc. a plan of their own specifications of their approval.

The monitor wells will be drilled with air. Diameter of hole will be 4 7/8". Casing will be 2" flush joint monitor casing with 10' of slotted monitor with a plug on bottom. Installed on top will be water tight locking caps with bolt down manhole. The well will also be gravel packed with bentonite grout on top. Cement curbing will be placed around each manhole.



These three wells are to be drilled to  $65^{\circ}$ . We will install monitor casing which is EPA specification. The cellar, once all operations have been completed to plug well bore, will be filled with cement. A dry hole marker will be installed on the Eugenie #2.

Your comments on this proposal would be appreciated. If you have any questions or comments please contact me at (505) 885-6663.

Sincerely.

George E. Parchman Manager



GP/lr