

Hill 30m 2

1355' FNL & 1785' FEL

Sec. 15, R-24S, T22E

Elk County, Colo. Mexico

11-5-79

Bone Springs: 6237' -
to 9434'

12 1/4" hole Whipstocked
@ 7197'

7 1/2" hole

13 3/8" 54.5" / 11, T-55 @ 592'

DV Tool @ 1931' - failed open
Squeeze w/ 300 sk CLH w/ 15" neat
200 sk CLH neat
Tested to 3000' - 30 min OK

- Top of live Cement @ 2999' cal
@ 75% eff.

- TOP of 7 5/8" Line @ 6740'

- TOP of CLH Neat @ 6874' cal

- 9 5/8" CSG Stopping @ 7022' { 2572' - 43 1/4" S-55
2190' - 40 1/4" S-55
2280' - 40 1/4" S-55
LTC
LTC

Cement to 7472' - 3572' cement job
(weight. Break down - lower zone)

- Top of 5" Line @ 9565'
12 1/4" hole to 9800'

7 5/8" R-110, Triple Seal jt line @ 9800'

6 1/2" hole

1079
6-10-1

TOKO
11376, 97, 98, 99, 111, 100

STRAWN
11376, 97, 98, 99, 111, 100 (10 holes) Acidizers
2000 gal 15% HCl

ATOS
11,646-50 - 2000 gal
Treatment
2000 gal ACID 15% HCl 2000 gal
11,610

ATOS
12,350-61
12,350-62
12,350-63
12,350-64
49'
Treatment
2000 gal 7 1/2" Wire 15% HCl 2000 gal
METHANOL-ACID 15% HCl
3300 gal 3300 gal methanol

TD - 12,710'

IPF - 200 MCF/DAY -
8-27-81 - F-173 MCF @ 170 BW/24 hr

11370 - 71' (4 holes)
11515-16 (4 holes) Squeezes

11732 - 11736' 11736'

5" 18 1/4" 11-30 triple seal line @ 12,707'