## N.M.O.C.D. COPY

DEPARTMENT OF TH		NIFED STATES INT OF THE IN DLOGICAL SURVE		Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM 32636	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				6. IF INDIAN, ALLOTTEE OR TRIBE NAME $M_{\rm AP} = 1980$	
				7. UNIT AGREEMENT NAME (). (). ().	
WELL X WELL OTHER 2. NAME OF OPERATOR				S. FARM OR LEASE NAME	
Delta Drilling Company				Amoco-Federal	
3. ADDIRESS OF OPERATOR P. O. Box 3467, Midland, Texas, 79702				9. WELL NO.	
<ul> <li>4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface</li> </ul>				10. FJELD AND POOL, OR WILDCAT Wildcat (Bone Springs) 11. SEC., T., E., M., OR BLE. AND SUBVEY OR ABEA	
1980/FNL 990/FEL				Sec 11, T-23-S, R-28-E	
14. PELMIT NO.		15. ELEVATIONS (Show whe 3004.5	ther DF, RT, GR, etc.)	12. COUNTY OB PARIS Eddy	New Mexico
16.	Check Appr	opriate Box To Indic	ate Nature of Notice, Report, or (	Other Data	
	NOTICE OF INTENTION TO: SUI				
TEST WATER SHUT		L OR ALTER CASING	WATER SHUT-OFF	REPAIRING	
FEACTURE TREAT SHOOT OR ACIDIZE		LTIPLE COMPLETE	SHOOTING OR ACIDIZING	ALTERING ABANDONM	
REPAIR WELL	СН	NGE PLANS	(Other) Setting 7-	5/8" Casing s of multiple completion	X
nent to this work	.) *		e locations and measured and true vertice 161 jts 7-5/8" casing as		
		Length	Depth		
KB		22	22		
130 jts.	K-55 26.4#	5299.92	5321.92		
-	N-80 26.4#	917.10	6239.02		
Float Co		2.12	6241.14		
1 jt. N-	80 26.4#	27.23	6268.37		
Guide Sh	oe	1.63	6270		
Cemented Tailed in	with 2200 SP n with 200 SP cement to pit	s. Class H wit	ith 6# salt, 3/4 of 1% C h 1/2 of 1% CFR-2, 5# sa ement with 10# brine. P to 1500 psi for 1 hr. fr plug at 5 p.m.	lt. Circulated	
	/				
18. I hereby certify th SIGNED $\frac{1}{1}$	<u>rr.</u> ]		Division Production Man	ager <sub>DATE</sub> 3/1	8/80
	deral or State office gd.) SIGNOF H			DATE HÀR	
CONDITIONS OF	APPROVAL, IF ANY	:			

## \*See Instructions on Reverse Side