

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

APR 18 1980

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" FORM C-101 FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER- ARTESIA, OFFICE	5a. Indicate Type of Lease State ☐ Fee ☒
2. Name of Operator AMINOIL USA, INC.	5. State Oil & Gas Lease No.
3. Address of Operator P. O. Box 10525, Midland, Texas 79702	7. Unit Agreement Name
4. Location of Well UNIT LETTER B 2310 FEET FROM THE East LINE AND 660 FEET FROM THE North LINE, SECTION 10 TOWNSHIP 24S RANGE 28E N.M.P.M.	8. Term of Lease Date Guitar
15. Elevation (Show whether DF, RT, GR, etc.) 2990.7 GL	9. Well No. 1
	10. Field and Pool, or Allotment Undes. Malaga Morrow
	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-3-80: Drilled 8-1/2" hole to 12,030'. Ran Schlumberger logs; FDC/CNL/GR/CAL, DLL/RXO from 12,030' to 9846'. Drilled 8-1/2" hole to 12,100'. Ran 57 jts. (2534.55') of 7-5/8", 39#, S-95, SFJ-P liner. Set shoe @ 12,098' w/top of Brown Oil Tools liner hanger @ 9564'. Halliburton cemented liner w/450 sx. Class 'H' w/0.6% HALAD 22, 0.4% CFR-2 & 3 lb. KCL per sx. Plug down @ 1:45 A.M. 4-4-80. WOC 29 hrs.

4-5-80: Drill out cmt. in 9-5/8" csg. from 8849' to 9564'. Pressure tested top of 7-5/8" liner w/1200 PSI surface pressure & 12.4 lb./gal. mud in hole.

4-6-80: Clean out inside liner. Drilled out cmt. to shoe. Tested w/1500 lb. surface pressure w/12.4 lb./gal. mud in hole. Displaced mud w/8.8 lb./gal. polymer mud & drill ahead w/6-1/2" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry L. Harper TITLE Operations Superintendent DATE 4/17/80

APPROVED BY W. A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE APR 21 1980

CONDITIONS OF APPROVAL, IF ANY: