

NEW MEXICO OIL CONSERVATION DIVISION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>H/B Oil Co.</i>		Lease <i>Rock tank 10 State</i>		Well # <i>1</i>	
Location of Well	Unit <i>A</i> <i>858 N</i> <i>1038 E</i>	Section <i>10</i>	Township <i>23</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor <i>Parker Drilling Co.</i>			Type of Equipment		

APPROVED CASING PROGRAM

* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>54.5</i>		<i>500</i>	<i>700 cins</i>
<i>12 1/4</i>	<i>9 5/8"</i>	<i>36</i>		<i>2500</i>	<i>1500 "</i>
<i>8 1/2"</i>	<i>5 1/2"</i>	<i>15.5</i>		<i>11700</i>	<i>850</i>

Casing Data:

Surface _____ joints of *9 5/8* inch *36* # Grade *K-55*

(Approved) (Rejected)

Inspected by *Mike Williams* date *2/14/80*

Cementing Program

Size of hole *12 1/4* Size of Casing *9 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *yes* Btm 3 jts welded *yes*

TD of hole *2500'* Set *2500'* Feet of *9 5/8* Inch *36* # Grade *K-55*

New-used csg. @ *2500'* with *2002* sacks neat cement around shoe

+ *1000* sack *Trinity Lite* additives *1/4 # flocc - 3 # gilsonite*

Plug down @ *11:20* (AM) (PM) Date *2/12/80*

Cement circulated *yes* No. of Sacks *279*

Cemented by *Williamson* Witnessed by *Mike Stillfield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

No centralizers

lasted by Drisk 2475'