

EXHIBIT "A"
SURFACE USE PLAN

Coquina Oil Corporation
Pure Gold "A" Federal No. 1
800' FSL & 1980' FWL
Sec. 21-23S-31E
Eddy Co., New Mexico

RECEIVED

JAN 23 1981

U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

This plan is submitted with Form 9-331C, Application for Permit to Drill, covering the above captioned well. The purpose of this plan is to describe the location of the proposed construction activity and operations plan, the magnitude of necessary surface disturbance involved, and the procedures to be followed in rehabilitating the surface after completion of the operation, so that a complete appraisal can be made of environmental impact associated with the drilling and operation of the well.

1. Exhibit "B" is a portion of USGS Nash Draw Quadrangle (Scale: 1:62,500) showing by the red line the route of access to the location. Exhibit "B" also depicts the topography and elevation of the land by contour lines (C.I. 10 feet), and roads in the vicinity of the proposed well. The well site is approximately 16 air miles east of Loving, New Mexico.

The location can be reached by driving west from Jal on State Hwy. 128 past the Lea-Eddy County line 5 miles. The location will be on the right (north) side of and adjacent to the highway.

Existing roads to be used as access to drill site are black top and no improvement or maintenance will be required.

2. An access road across Federal surface will measure 12' x 50' and will cross parts of the SE/4 of the SW/4. We will grade up approximately a 6" crown with shallow bar ditches on either side. Caliche, if required, will be obtained from an existing borrow pit located in the NE/4 NE/4 Sec. 29-23S-31E, on Federal land. The roadway will be essentially level and will cause no drainage problems. A cattle guard will be installed at the highway exit.
3. Exhibit "D" is an area plat on a scale of 1" = 4000', showing existing wells within a two mile radius of the proposed well.
4. At the present time Coquina neither owns nor controls any facilities within one mile of the proposed well.

If well is found to be productive, presumably of gas, it will be necessary to install a flowline from the wellhead to a gas production unit and meter run which will be located on the drill site pad. A small flare pit, approximately 30' x 30' may be required, and if constructed, will be fenced with sheep-tight fence to protect livestock and wildlife. Should the well be productive of oil and condensate, product storage tanks will be required, and can likewise be erected on the well site pad.

Portions of the drill site pad not required for producing operations, if any, will be restored as closely as possible to original ground contours and seeded with native grasses as directed by BLM.