

4/5F
File ✓

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well gas well other **SEP 22 1980**

2. NAME OF OPERATOR
Amoco Production Company **O. C. D.**

3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240 **ARTESIA, OFFICE**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL X 1980' FEL
AT TOP PROD. INTERVAL: (Unit J, NW/4, SW/4)
AT TOTAL DEPTH:

5. LEASE
NM-25953

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal AI Com.

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
34-24-28

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3006.9 GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON*
- (other)

SUBSEQUENT REPORT OF:

-
-
-
-
-
-
-
-

RECEIVED

SEP 17 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a TD of 12310' and ran 39# S-95 7-5/8" casing set at 12309'. Top of liner at 9387'. Cemented with 100 SX Trinity Lite cement with additives and with 475 SX Class H cement with additives. Plugged down at 1:30 p.m. 8-31-80 with 1350#. Cement did not circulate. Set a retainer at 8710'. Squeezed top of liner with 200 SX Class H cement with additives. Squeeze completed 7:00 p.m. 9-30-80. WOC 18 hr. Drilled cement off top of liner. Tested liner with 1500# for 30 min. Test OK. Reduced hole to 6-1/2" and resumed drilling.

ACCEPTED FOR RECORD

GW

SEP 18 1980

U.S. GEOLOGICAL SURVEY

ARTESIA, NEW MEXICO

DATE 9-18-80

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Benton Green TITLE Ast. Adm.

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

- 0+4-USGS, A
- 1-Hou
- 1-Susp
- 1-LBG
- 1-W. Stafford, Hou
- 1-HNG
- 1-Pecos Irr.
- 1-Union Oil of Calif.
- 1-R. Enfield
- 1-John Kochergen