NO. OF COPIES RECEIVED	3	
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

DEC 16 1980

O. C. D.

ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease: State [X] Fee [ ]

5. State Oil & Gas Lease No.: LG-6544

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT —" FOR SUCH PROPOSALS.)

7. Unit Agreement Name:

1. OIL WELL [ ] GAS WELL [XX] OTHER-

8. Farm or Lease Name: State IB Com.

2. Name of Operator: Amoco Production Company ✓

9. Well No.: 1

3. Address of Operator: P. O. Box 68 Hobbs, NM 88240

10. Field and Pool, or Wildcat: Und. Morrow

4. Location of Well: UNIT LETTER N, 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 31 TOWNSHIP 23-S RANGE 25-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.): 3881.1' GL

12. County: Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [ ]
- TEMPORARILY ABANDON [ ]
- PULL OR ALTER CASING [ ]
- PLUG AND ABANDON [ ]
- CHANGE PLANS [ ]
- OTHER [ ]

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [ ]
- COMMENCE DRILLING OPNS. [ ]
- CASING TEST AND CEMENT JOB [ ]
- ALTERING CASING [ ]
- PLUG AND ABANDONMENT [ ]
- OTHER [ ]

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Flow tested two days and recovered no oil and no gas. Ran bottom hole pressure test. Set a cement retainer at 10330'. Squeezed Morrow perforations 10404'-10418' with 100 SX Class H cement (with 6% fluid loss additive.) Reversed out two SX. Drilled through cement to 10450'. Drilled cast iron bridge plug from 10450-10490'. Set a cement retainer at 10436'. Squeezed perforations 10462-10481' with 100 SX Class H cement with additives. Reversed out 24 SX cement. Drilled through retainer and cement to 10560'. Perforated 10496'-10544' with 2 JSPF. Acidized with 8000 gal. 7-1/2% MS acid with additives. Currently swab testing.

0+4-NMOCD, A 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Benton Greer TITLE Assist. Admin. Analyst DATE 12-10-80

APPROVED BY Mike Williams TITLE SUPERVISOR, DISTRICT II DATE DEC 18 1980

CONDITIONS OF APPROVAL, IF ANY: