

Belco Petroleum Corporation
Guitar Estate Comm #1
Drilling Operations

4/3/80 SPUDDED 8:15 AM, 4/2/80. MW 8.6, V 35. 1/2 deg @ 200', 1 deg @ 440'. RU & ran csg. Very tight. Unable to get pipe below 368'. NMOCC says OK below 350'.

4/4/80 Drlg 630'. MW 10.0. 3/4 deg @ 944'.

4/5/80 Drld to 1340'. MW 10.0. 3/4 deg @ 1150'.

4/6/80 Drlg 1785'. 3/4 deg @ 1705'. MW 10.0.

4/7/80 Drlg 2273'. 2 deg @ 2200'. MW 10.0.

4/8/80 Depth 2420'. Ran csg, Delaware 1m. 10 3/4" csg. MW 10. 1 3/4 deg @ 2420'.

4/9/80 Drlg 2445'. MW 9.5. Cmt'd w/Dowell. Tstd csg 1500 psi, OK. Cmt'd w/2000 sx 65-35 Poz w/10# salt + 1/4# cellophane per sk. Tailed in w/300 sx Cl C w/2% CaCl₂ + 10# salt per sk. Circ out 300 sx.

4/10/80 Drlg 3225'. MW 9.3.

4/11/80 Drlg 3832'. MW 9.4. 1 1/4 deg @ 3390'.

4/12/80 Drlg 4490'. MW 9.6. 1 deg @ 3900'. 1 deg @ 4381'.

4/13/80 Drlg 5156'. MW 9.4. 3/4 deg @ 4880'.

4/14/80 Drlg 5660'. MW 9.4. 3/4 deg @ 5324'.

4/15/80 Drlg 6130'. MW 9.4.

4/16/80 Drlg 6500'. MW 9.5. 1 1/4 deg @ 6270'. DST #1 5340-6545'.

4/17/80 Drlg 6575'. MW 9.4.