


STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501



Form C-103
Revised 10-1-7

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-4683

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
Amoco Production Company ✓
3. Address of Operator
P.O. Box 68, Hobbs NM 88240
4. Location of Well
UNIT LETTER J 1980 FEET FROM THE East LINE AND 1880 FEET FROM
THE South LINE, SECTION 26 TOWNSHIP 24 S RANGE 27-E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.)
3220' KB
12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to PKA as follows:
Notify NMOC 24 hrs prior to MTSU. POH with rods, pump, and thg. RIH with CIBP, set at 3700' in 9 5/8" csg. Cap with 25 sxs class "C" neat. This will bring cmt up to 3617', top of Delaware 2416', top of perms 3805'. Displace hole with salt gel mud. POH. RIH and perf 2432-34' w/45PF using a 4" gun. RIH with thg and pkr, set pkr at 2325'. Establish inj rate and pull thg and pkr. RIH with thg and cmt retainer, set at 2325'. Squeeze with 700 sxs Class "C" neat, circ. to surface. Leave 33 sxs in 9 5/8" csg
0+5 NMOC, A 1-J.R. Barnett, Don 1-F.J. Nash, Don 1-GCC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Larry C. Clark TITLE Asst. Admin. Analyst DATE 11-12-84

APPROVED BY ORIGINAL SIGNED BY LARRY BROOKS TITLE GEOLOGIST - NMOC DATE NOV 20 1984

CONDITIONS OF APPROVAL, IF ANY:

below retainer to give a 50' plug above and below $13\frac{3}{8}$ ' shoe at 2382'. With the spot a 31 sx (100') plug from 450'-350'. This will give a 50' plug above and below 20" esp shoe at 400'. With the spot a 10 sx surface plug from 32' to surf. Cap well and erect abandonment marker.