United States Department of the Interior

RECEIVED

GEOLOGICAL SURVEY
P. O. Drawer U
Artesia, New Mexico 88210

APR 9 1980

O. C. D.

April 8, 1980

Union Oil Company of California P. O. Box 71 Midland, Texas 79702

Gentlemen:

UNION OIL COMPANY OF CALIFORNIA Fed "AJ" No. 1 1650 FNL 2310 FEL Sec. 10 T.22S R.27E

Lease No. NM 0454018

Above Data Required on Well Sign

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 4,500 feet to test the Delaware formation is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

Eddy County

- 1. Drilling operations authorized are subject to compliance with the GENERAL REQUIREMENTS FOR OIL AND GAS OPERATIONS ON FEDERAL LEASES, dated July 1, 1978.
- 2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the SURFACE USE PLAN and this approval including the GENERAL REQUIREMENTS.
- 3. All access roads will be limited to a 12 foot wide driving surface, excluding turnarounds. Surface disturbance associated with road construction will be limited to 20 feet in width.
- 4. Submit a Daily Report of Operations from spud date until the Well Completion Report (form 9-330) is filed. The progress report should be not less than 8" x 5" in size and each page should identify the well.
- 5. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Requirements. The color used should simulate Sandstone Brown (Federal Standard No. 595A, color 20318 or 30318).
- 6. Notify the Survey by telephone 24 hours prior to spudding well.
- 7. Cement behind the 8-5/8" and 5-1/2" casing must be circulated.
- 8. Notify Survey in sufficient time to witness the cementing of the 8-5/8" and 5-1/2" casing.