

Phillips Petroleum Compa
Malaga A No. 2
Form C-105, Item 28 (Cont'd)

<u>Csg Size</u>	<u>Weight Lb/Ft.</u>	<u>Depth Set</u>	<u>Hole Size</u>	<u>Cementing Record</u>
9-5/8"	40#, K-55, N-80	9500'	12-1/4"	<u>1st stage</u> - cmt w/800 sxs Cl"H" w/20% DD, 3# salt, 5# Gilsonite, 1/4# celloseal, Tail w/300 sxs Cl "H" w/5# Gilsonite, 1/4# cellosea Circ 150 sxs to surface. <u>2nd stage</u> - cmt w/1850 sxs Cl "H" w/20% DD, 5# Gilsonite, 1/4# cell seal. Tail w/150 sxs Cl"H" + 2% LWL. Circ 350 sxs to surface.
5-1/2"	23#, 20#, 17#,N-80	13,050'	8-1/2"	w/1600 sxs Cl"H" w/1.5% CF9, 2% WR-10, 2% KCL, TOC 8390'

Formation Record (con't)

<u>From</u>	<u>To</u>	<u>Thickness</u>	<u>Formation</u>
10,724	10,782	58	Lime
10,782	10,865	83	Lime & Shale
10,865	11,076	211	Lime
11,076	11,534	458	Shale & Lime
11,534	11,606	72	Shale
11,606	11,648	42	Lime & Shale
11,648	11,698	50	Shale
11,698	11,747	49	Lime & Shale
11,747	11,832	85	Shale
11,832	11,893	61	Shale & Lime
11,893	11,934	41	Shale
11,934	11,963	29	Lime & Shale
11,963	13,051	1088	Shale