

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
MAY 26 1980
O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-4205

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator GULF OIL CORPORATION	8. Farm or Lease Name Eddy "C" State
3. Address of Operator P. O. Box 670, Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> 1980 FEET FROM THE <u>North</u> LINE AND 1980 FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>22S</u> RANGE <u>28E</u> NADP	10. Field and Pool, or Wildcat Undes. Indian Flats Morrow
11. Elevation (Show whether DF, RT, GR, etc.) 3157' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Cement (Crooked Hole)</u> <input checked="" type="checkbox"/>

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 1640', crooked hole. POH & GIH open-ended, Halco cemented w/350 sacks "H" w/7# salt/sack and 2% CaCl₂. POH to 1300', rec out 50 sacks cement. WOC 12 hrs. GIH & drill off cement plug @ 1470'. Round trip and change bottom hole assembly @ 1703'. New hole dev 3° at 1703'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED N. B. Sikes Jr. TITLE Area Engineer DATE 5-22-80

APPROVED BY W. A. Gussett TITLE SUPERVISOR, DISTRICT H DATE MAY 27 1980

CONDITIONS OF APPROVAL IF ANY: