1-BH-FLD CLK	CISE
CARY-MIDLAND STARRAK-TULSA Form 9-331 Dec. 1973 FILE	PY Form Approved. Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-25876
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas well well well gas	<u>Gettý Federal "24"</u> 9. WELL NO.
2. NAME OF OPERATOR	
GETTY OIL COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Wild Cat-Beta-Prospect
P.O. Box 730, Hobbs, N.M. 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	
below.) AT SURFACE: Ltr. G, 1980 FNL & 1980 FEL	Sec. 24, T-22-S, R-31-E 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Eddy N.M.
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
Reform, on other bank	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3574.2 GL
REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         TEST WATER SHUT-OFF       X         FRACTURE TREAT       Image: Constraint of the second s	(NOTE: Report results in riulional generation or zone change on the grad of the letion or zone
MULTIPLE COMPLETE	U.S. GEULUGIUAL SURVEY ARTESIA, NEW MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta	
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. 5 jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" mement 1200 sxs. Circulated 250
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. 5 jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" mement 1200 sxs. Circulated 250
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. 5 jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 1 2% CaCl and 300 sxs. Class "C" mement 1200 sxs. Circulated 250 for 30 min. O.K.
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. 5 jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" ement 1200 sxs. Circulated 250 for 30 min. O.K. RECEIVED JUN 13 1980 O. C. D.
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c sxs. of cement WOC 18 Hrs. tested to 1200# f	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. 5 jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" ement 1200 sxs. Circulated 250 for 30 min. O.K. RECEIVED JUN 13 1980 O. C. D.
<ul> <li>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine.</li> <li>Sharp Drilling Company spudded 17 1/2" hole</li> <li>6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&amp;C casing and set @ 891', Western cement Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c sxs. of cement WOC 18 Hrs. tested to 1200# f</li> <li>Subsurface Safety Valve: Manu. and Type</li></ul>	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. 5 jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" ement 1200 sxs. Circulated 250 for 30 min. O.K. RECEIVED JUN 13 1980 O. C. D.
<pre>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&amp;C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c sxs. of cement WOC 18 Hrs. tested to 1200# f Subsurface Safety Valve: Manu. and Type</pre>	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" mement 1200 sxs. Circulated 250 for 30 min. O.K. RECEIVED JUN 13 1980 O. C. D. METESA OFFICE Ft.
<pre>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Sharp Drilling Company spudded 17 1/2" hole 6/9/80 Drilled 17 1/2" hole to 891'. Ran 23 8RD ST&amp;C casing and set @ 891', Western cem Class "C" Cement w/1/4# Flocele, 4% Gel and cement w/1/4# Flocele and 2% CaCl. Total c sxs. of cement WOC 18 Hrs. tested to 1200# f Subsurface Safety Valve: Manu. and Type</pre>	directionally drilled, give subsurface locations and ent to this work.)* 7:00 PM, June 5, 1980. jts. (865') 13 3/8" OD H-40 48# mented 13 3/8" casing w/900 sxs. 2% CaCl and 300 sxs. Class "C" mement 1200 sxs. Circulated 250 for 30 min. O.K. RECEIVED JUN 13 1980 O. C. D. METESA OFFICE Ft.

•

/