

5-USGS-ARTESIA
1-MR. FRANKA-TULSA
1-MR. A. CARY-MIDLAND
1-POGO, MIDLAND
1-POGO, HOUSTON
1-CB, FOREMAN
1-BH, FIELD CLK
1-JDM, ENGR.
1-FILEForm Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit ltr. G, 1980' FNL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED

JUL 18 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JUL 21 1980

O.C.D.
ARTESIA OFFICE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/11/80 Drilled 8 1/2" hole to 12,247'. Ran 296 jts. (12,219') 7" OD 26# csg. and set at 12,242' with Howco DV tool at 7484-7487'. Howco cemented first stage with 500 sxs Lite with 6/10% Halad 22, 3# gilsonite, and 1/4# flocl; tailed in with 200 sxs Class "H" with 8/10% Halad 22 and 3# salt/sx. Did not circulate cement. Second stage: Howco cemented with 1300 sxs Lite, 6/10% Halad 22, 3# gilsonite, and 1/4# flocl; tailed in with 200 sxs Class "H" with 8/10% Halad 22 and 3# salt/sx. Plug down at 5:00 p.m. 7-11-80. Circulated 30 sxs cement. Total cement 2200 sxs. WOC 18 hrs. Tested csg. to 1200# for 30 min. OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Supt. DATE 7/14/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE DISTRICT ENGINEER
CONDITIONS OF APPROVAL, IF ANY:

JUL 18 1980

BH/de

*See Instructions on Reverse Side