

NO. OF INTERESTED PARTIES	
DISTRIBUTION	
SANTA FE	1
FILE	11 ✓
U.S.G.B.	
LAND OFFICE	
OPERATOR	1

RECEIVED
 O CONSERVATION DIVISION
 P. O. BOX 2088
 SANTA FE, NEW MEXICO JUL 01 7 1980

Form C-103
 Revised 10-1-78

O. C. D.
 ARTESIA, OFFICE

5a. Indicate Type of Lease
 State ☐ Free ☒
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CEMENT OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
 Belco Petroleum Corporation
 Address of Operator
 411 Petroleum Building Midland, Texas 79701
 Location of well

7. Unit Agreement Name

8. Farm or Lease Name

Lakey Corn

9. Well No.

1

10. Field and Pool, or Wildcat

Und North Loving Morrow

UNIT LETTER L 2280 FEET FROM THE South LINE AND 660 FEET FROM
 THE West LINE, SECTION 20 TOWNSHIP 23-S RANGE 28-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
 3060' GL

12. County
 Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐
 OTHER ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐
☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOBS ☐
 OTHER ☒ Drilling Operations

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/16/80 SPUDDED 6/15/80. WOC @ 450'. Ran 11 jts 16" 65#, H-40, ST&C csg, set @ 450'. Cmt'd w/750 sx Cl C w/2% CaCl₂. Circ out 150 sx. 2 deg @ 450'. WOC 19 1/4 hrs. Tstd csg to 600 psi.
 6/17/80 Drlg 1137' anhy. 1/2 deg @ 730'.
 6/18/80 Drlg 1810' sd & anhy. 1 deg @ 1230', 1 3/4 deg @ 1730'.
 6/19/80 Drlg 2302' anhy. 1 3/4 deg @ 2250'.
 6/20/80 WOC @ 2415' Delaware lm. Ran 63 jts 10 3/4", 40.5#, K-55, ST&C, set @ 2415'. Cmt'd w/1875 sx Howco lite w/10# salt & 1/4# flocele. Tailed in w/300 sx Cl C w/10# salt & 2% CaCl₂. Circ out 200 sx. WOC 20 1/2 hrs. Tstd csg to 1500 psi.
 6/21/80 Drlg 2890' anhy.
 6/22/80 Drlg 3470' lm & sd.
 6/23/80 Drlg 4180'. lm & sd.
 6/24/80 Drlg 4703' lm,sh & sd. 2 1/2 deg @ 4430'.
 6/25/80 Drlg 5180' lm & sd. 2 1/2 deg @ 4990'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE District Engineer DATE July 2, 1980

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR

DATE JUL 8 1980

CONDITIONS OF APPROVAL, IF ANY: