

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LB-5172

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT STRATUM. USE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

AUG 11 1980

O. C. D.  
ARTESIA, OFFICE

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Amoco Production Company
3. Address of Operator P. O. Box 68 Hobbs, NM 88240
4. Location of Well UNIT LETTER <u>G</u> 1980 FEET FROM THE <u>North</u> LINE AND 1980 FEET FROM THE <u>East</u> LINE, SECTION <u>1</u> TOWNSHIP <u>24-S</u> RANGE <u>24-E</u> NMPM.

7. Unit Agreement Name
8. Farm or Lease Name State IN
9. Well No. 1
10. Field and Pool, or Wildcat Und. Morrow
12. County Eddy

15. Elevation (Show whether DF, RT, GR, etc.)  
3936.7 GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 2700' and ran 36# K-55 9-5/8" casing set at 2700'. Cemented with 1300 SX lite 10# <sup>gel cement</sup> cement with 1/4# Flocele/SX and 250 SX Class C cement with 2% CACL. Plugged down at 8:45 p.m. 7-12-80. Circulated 190 SX. WOC 19 hr. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

0+5-NMOCD, A 1-Hou 1-Susp 1-LBG 1-Superior  
1-Moncrief 1-El Paso 1-Maralo 1-Hibbert 1-Scott

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Administrative Analyst DATE 7-31-80

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE AUG 12 1980

CONDITIONS OF APPROVAL, IF ANY: