

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

8-21-80

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LB-5172	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <u>ACQUA, OFFICE</u>		7. Unit Agreement Name
2. Name of Operator Amoco Production Company ✓		8. Farm or Lease Name State IN
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> 1980 FEET FROM THE <u>North</u> LINE AND 1980 FEET FROM THE <u>East</u> LINE, SECTION <u>1</u> TOWNSHIP <u>24-S</u> RANGE <u>24-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Und. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3936.7 GL		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 10880' and ran 3115' of 17# N-80 5-1/2" casing and 8765' of N-80 and K-55 15-1/2# 5-1/2" casing set at 10880'. Cemented with 1600 SX Trinity Lite cement with .75% CFR2 and 1/4# Flocele/SX and with 615 SX Class H cement with .75% CFR2 and 5# KCL/SX. Plugged down at 7:05 p.m. 8-8-80. Ran temp. survey. Top of cement at approx. 2620'. Will test casing when completion unit is moved in.

0+4-NMOCD, A 1-Hou 1-Susp 1-LBG 1-Wayne Stafford, Hou 1-Moncrief
1-El Paso 1-Maralo 1-Hibbert 1-Scott 1-Superior

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Administrative Analyst DATE 8-21-80

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE AUG 25 1980

CONDITIONS OF APPROVAL, IF ANY: