	Fa-a ( 10)
DISTRIBUTION P. O. BOX 2088	Form C-10 Revised 19
SANTA FE SANTA FE, NEW MEXICO 875 APR 1 7 1981	5a. Indicate Type of Lease
U.S.G.S.	State X Fee
LAND OFFICE O. C. D.	5. State Otl & Gas Lease No.
ARTESIA, OFFICE	L-4682
SUNDRY NOTICES AND REPORTS ON WELLS	
DO NOT USE THIS FOR PROPOSALS TO PHILL O AND AT DEEPEN OR FUG DAX TO A DIFFEHENT RESERVOIR.	
	7, Unit Agreement Name
OIL CAS WELL OTHER-	8. Farm or Lease Name
ame of Operator	State IS
moco Production Company	9, Well No.
. O. Box 68, Hobbs, NM 88240	1
ocation of Well	10. Field and Pool, or Wildcat
F 1980 North 660	Wildcat Delaware
THE West LINE, SECTION 25 TOWNSHIP 24-S RANGE 27-E NMPN	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Eddy
11111111111111111111111111111111111111	
Check Appropriate Box To Indicate Nature of Notice, Report or O	
NOTICE OF INTENTION TO:	T REPORT OF:
PLUG AND ABANDON	ALTERING CASING
	PLUG AND ABANDONME
APOMARILY ABANDON	•
The second state operations (Clearly state all pertinent details, and give pertinent dates, includin	g estimated date of starting any pro-
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1103.	g estimated date of starting any pro
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) see RULE 1703. Deen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. Deer the following:	ductor pipe had en reduced and
work) see RULE 1703. Prilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. Der the following:	ductor pipe had en reduced and
work) see RULE 1703. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. Der the following: Set a 100-sack Class C cement plug from 600'-500'.	ductor pipe had en reduced and
work) see RULE 1703. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. Der the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'.	ductor pipe had en reduced and
<pre>work) see ROLE 1703. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con even set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. ever the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'.</pre>	ductor pipe had en reduced and
<pre>work) see ROLE 1703. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con meen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. mer the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'.</pre>	ductor pipe had en reduced and
<pre>work) see ROLE 1703. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con even set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. ever the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'.</pre>	ductor pipe had en reduced and
<pre>work) see RULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. Der the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40'</pre>	ductor pipe had en reduced and Plugged hole
<pre>work) see RULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. ber the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin</pre>	ductor pipe had en reduced and Plugged hole
<pre>work) see RULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. Der the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40'</pre>	ductor pipe had en reduced and Plugged hole
<pre>work) see RULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. ber the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin</pre>	ductor pipe had en reduced and Plugged hole
<pre>work) see RULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con been set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. ber the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin</pre>	ductor pipe had en reduced and Plugged hole
<pre>work) see NULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con neen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. neer the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set a 100-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin moved off the State IS No. 1-Y. Dr44-NMOCD, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-LBG -Internorth</pre>	ductor pipe had en reduced and Plugged hole g rig has
<pre>work) see NULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con heen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. her the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin moved off the State IS No. 1-Y.</pre>	ductor pipe had en reduced and Plugged hole g rig has
<pre>work) see NULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con heen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. her the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin moved off the State IS No. 1-Y. Dr44-NMOCD, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-LBG -Internorth I hereby certify that the information above is true and complete to the best of my knowledge and belief.</pre>	ductor pipe had en reduced and Plugged hole g rig has 1-HNG
<pre>work) see NULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con neen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. neer the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set a 100-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin moved off the State IS No. 1-Y. Dr44-NMOCD, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-LBG -Internorth</pre>	ductor pipe had en reduced and Plugged hole g rig has 1-HNG
<pre>work) see NULE 1103. Drilled to a TD of 708' and lost bit and fishing equipment. (30" con heen set at 39'. A 17-1/2" hole had been drilled to 194'. Bit was th 15-1/2" hole was drilled to 708'.) Top of fish is at approx. 600'. her the following: Set a 100-sack Class C cement plug from 600'-500'. Set a 100-sack Class C cement plug from 500'-400'. Set a 100-sack Class C cement plug from 400'-300'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 300'-200'. Set a 100-sack Class C cement plug from 200'-110' Set an 80-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug from 110'-40' Set a 130-sack Class C cement plug to surface. Welded cap on. Will install 4" P X A marker after drillin moved off the State IS No. 1-Y. Dr44-NMOCD, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-LBG -Internorth I hereby certify that the information above is true and complete to the best of my knowledge and belief.</pre>	ductor pipe had en reduced and Plugged hole g rig has 1-HNG