

Form 9-331
Dec. 1973

RECEIVED BY

DEC 26 1984

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
O. C. D.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
InterNorth Inc.

3. ADDRESS OF OPERATOR
10,000 Old Katy Rd., Houston, Texas 77055

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1570' FNL & 480' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
NM 36610

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Azotea Mesa Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Robina Draw (Morrow)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 6, T-23-S, R-24-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.
30-015-23439

15. ELEVATIONS (SHOW DF, KDB, AND WD)
GL 4243, KB 4259

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Bridge plug set at 10,430'. Perforations above BP located at 10,160' - 10,322'.

Plugging procedure: Operations started 6/15/84

1. Spotted 15 sx cl H cmt from 10,150' - 10,500'.
2. Cut 5½ csg. at 4110' and pulled.
3. Spotted 25 sx cl H cmt at 4175' - 4060'. Tagged top of plug at 4055'.
4. Spotted 35 sx cl H cmt. plug from 2570' - 2470'. Tagged top of cement plug at 2465'.
(Continued on back page)

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jo Ann Randall

TITLE

Production Accountant

July 18, 1984

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

12-21-84

Post ID-2
1-4-85
P+H

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

InterNorth Inc.
Azotea Mesa Fed. #1
Sec. 6, T-23-S, R-24-E
1570' FNL & 480' FEL

5. Spotted 30 sx cmt plug from 500' to 400'.
6. Spotted 10 sx cmt plug in top of csg. Cut off 3' below ground level & welded 1/2" steel plate on top of csg. & installed 4" marker.
7. Broke out production facilities. Moved all equipment from lease site. Cleaned location and planted grass seed. Well P&A 6/23/84.